









DDP (Defab Duraproofing Process) Two-way Ripstop Construction

Built for Local Conditions



Heavy-weight, industrial strength 100% core spun canvas.

Guaranteed protection from the most arduous weather, road and terrain conditions.



Suitable for heavy-weight applications such as heavy duty long haul road transport, fixed frame canopies, car tarps, trailer covers and Ute/4WD canopy covers as well as machinery covers. Tearlok® Bison II can also be used for hire/builder tarpaulins, heavy duty seat covers and a great deal of general canvas goods applications.

PROPERTIES

	Shrink Resistant	
	Waterproof	
(UV)	UV Resistant	
	Mould and Algae Resistant	
	Breathable	
	Tear Resistant	
To	Abrasian Resistant	

5	5-Year Guarantee
205	Width available (cm)

SPECIFICATIONS

Composition	52% Polyester / 48% Cotton
Weight	640gsm (14oz loomstate, 17oz proofed)
Width	205cm
Roll Length	40 m
Roll Weight	52kg
Tensile Strength (Warp)	2900N
Tensile Strength (Weft)	2900N
Tear Resistance (Warp)	180N
Tear Resistance (Weft)	130N
Shrinkage	<2% warp & <1% weft
Water Resistance	10kPa
Cone Leakage	Pass
Rub Fastness	Dry 4, Wet 5

Local sales 1300 785 322



Weaving history since 1976

30 Somerton Park Drive Campbellfield VIC 3061

T+61 3 9305 3988 F+61 3 9305 1377 E canvas@defab.com.au **defab.com.au**











