



DDP (Defab Duraproofing Process)



Ripstop Construction



Built for Local Conditions

tearlok®
boulder









Mid-weight 52/48 polyester cotton proofed canvas. With core spun yarn ripstop.


Budget-priced but constructed to provide higher than normal tear and tensile strength.

tearlok[®] boulder

Suitable for applications of medium to heavy weight such as fixed frame canopies, car tarps, trailer covers and Ute/4WD canopy covers as well as machinery covers. Tearlok[®] Boulder can also be used for hire/builder tarpaulins, heavy duty seat covers and a great deal of general canvas goods applications.

PROPERTIES

	Shrink Resistant
	Waterproof
	UV Resistant
	Mould and Algae Resistant
	Breathable
	Tear Resistant
	Fire Retardant Available
	Environmentally Friendly

 5-Year Guarantee

 Width available (cm)

SPECIFICATIONS

Composition	52% Polyester / 48% Cotton
Weight	595gsm (12oz loomstate, 17oz proofed)
Width	205cm
Roll Length	40m
Roll Weight	49kg
Tensile Strength (Warp)	2400N
Tensile Strength (Weft)	2100N
Tear Resistance (Warp)	125N
Tear Resistance (Weft)	80N
Shrinkage	<2% warp & <1% weft
Water Resistance	10kPa
Cone Leakage	Pass
Rub Fastness	Dry 4-5, Wet 4

Local sales **1300 785 322**

 **defab[®]**
Weaving history since 1976

30 Somerton Park Drive
Campbellfield VIC 3061

T +61 3 9305 3988
F +61 3 9305 1377
E canvas@defab.com.au
defab.com.au

