



DDP (Defab Duraproofing Process)



Built for Local Conditions



Environmentally Friendly

**tearlok**®  
eyre







**Mid-weight 52/48 polyester cotton proofed canvas.**


Durable and budget-oriented treated canvas available in a range of solid colours with versatile application.


# tearlok<sup>®</sup> eyre

Suitable for applications of fixed frame canopies, swags, trailer and canopy covers, as well as machinery covers. Tearlok<sup>®</sup> Eyre can also be used for industrial curtains, canvas partitions and a great deal of general canvas goods applications.

## PROPERTIES

	Shrink Resistant
	Waterproof
	UV Resistant
	Mould and Algae Resistant
	Breathable
	Tear Resistant

 5-Year Guarantee

 Width available (cm)

## SPECIFICATIONS

Composition	52% Polyester / 48% Cotton
Weight	595gsm (12oz loomstate, 17oz proofed)
Width	205cm
Roll Length	40m
Roll Weight	49kg
Tensile Strength (Warp)	2900N
Tensile Strength (Weft)	2100N
Tear Resistance (Warp)	185N
Tear Resistance (Weft)	143N
Shrinkage	<2% warp & <1% weft
Water Resistance	14kPa
Cone Leakage	Pass
Rub Fastness	Dry 4-5, Wet 4

Local sales **1300 785 322**

 **defab<sup>®</sup>**  
Weaving history since 1976

30 Somerton Park Drive  
Campbellfield VIC 3061

T +61 3 9305 3988  
F +61 3 9305 1377  
E [canvas@defab.com.au](mailto:canvas@defab.com.au)  
[defab.com.au](http://defab.com.au)

