



DDP (Defab Duraproofing Process)



Built for Local Conditions



Environmentally Friendly

tearlok®
hume






Mid-weight 52/48 polyester cotton proofed canvas.


Durable and budget-oriented treated canvas available in a range of solid colours with versatile application.

tearlok[®] hume

Suitable for applications of fixed frame canopies, swags, Trailer and canopy covers, as well as machinery covers. Tearlok[®] Hume can also be used for industrial curtains, canvas partitions and a great deal of general canvas goods applications.

PROPERTIES

-  Shrink Resistant
-  Waterproof
-  UV Resistant
-  Mould and Algae Resistant
-  Breathable
-  Tear Resistant
-  Fire Retardant Available

 5-Year Guarantee

 205 Width available (cm)

SPECIFICATIONS

Composition	52% Polyester / 48% Cotton
Weight	590gsm (12oz loomstate, 18oz proofed)
Width	205cm
Roll Length	40m
Roll Weight	48kg
Tensile Strength (Warp)	2600N
Tensile Strength (Weft)	2200N
Tear Resistance (Warp)	170N
Tear Resistance (Weft)	93N
Shrinkage	<2% warp & <1% weft
Water Resistance	10kPa
Cone Leakage	Pass
Rub Fastness	Dry 4-5, Wet 4

Local sales **1300 785 322**

 **defab[®]**

Weaving history since 1976

30 Somerton Park Drive
Campbellfield VIC 3061

T +61 3 9305 3988
F +61 3 9305 1377
E canvas@defab.com.au
defab.com.au

