



DDP (Defab Duraproofing Process)



Ripstop Construction



Built for Local Conditions

**tearlok**®  
oxen









**Mid-weight 52/48 polyester cotton proofed canvas. With core spun yarn ripstop.**


Guaranteed protection from the most arduous weather, road and terrain conditions.

# tearlok<sup>®</sup> oxen

Suitable for applications of medium to heavy-weight such as fixed frame canopies car tarps, trailer covers and Ute/4WD canopy covers as well as machinery covers. Tearlok<sup>®</sup> Oxen can also be used for hire/builder tarpaulins, heavy-duty seat covers and a great deal of general canvas goods applications.

## PROPERTIES

	Shrink Resistant
	Waterproof
	UV Resistant
	Mould and Algae Resistant
	Breathable
	Tear Resistant
	Fire Retardant Available
	Environmentally Friendly

 5-Year Guarantee

 Width available (cm)

## SPECIFICATIONS

Composition	52% Polyester / 48% Cotton
Weight	600gsm (13oz loomstate, 18oz proofed)
Width	205cm
Roll Length	40m
Roll Weight	49kg
Tensile Strength (Warp)	2900N
Tensile Strength (Weft)	2100N
Tear Resistance (Warp)	170N
Tear Resistance (Weft)	131N
Shrinkage	<2% warp & <1% weft
Water Resistance	10kPa
Cone Leakage	Pass
Rub Fastness	Dry 4-5, Wet 4

Local sales **1300 785 322**

 **defab<sup>®</sup>**

Weaving history since 1976

30 Somerton Park Drive  
Campbellfield VIC 3061

T +61 3 9305 3988  
F +61 3 9305 1377  
E canvas@defab.com.au  
**defab.com.au**

